



## Durasyn® 133

**Technical Data Sheet** 

**Durasyn 133 polyalphaolefin** is a fully synthesized distilled and hydrogenated hydrocarbon base fluid produced from linear alphaolefin feed stocks. Its engineered physical and performance properties are designed to extend the service life and enhance the performance of fully formulated lubricants operating under continuous low, high, or wide temperature range conditions.

## **Prospective Applications**

- Electric vehicle axel and transmission fluid
- Traditional ICE vehicle motor oil
- Immersion cooling thermal fluid
- Rerefined oil performance improver

## Compatibility

Durasyn 133 has been engineered to be either near or direct substitutes for existing PAO base oils and premium quality mineral oils. Compatibility with metals, elastomers, coatings, and sealants is similar to fully synthesized PAO base oils. Solubility also closely matches other fully synthesized hydrocarbon base oils.

## **Specifications**

Property	Typical Value	Test Method
Viscosity at 100°C (cSt)	3.4	ASTM D445
Viscosity at 40°C (cSt)	13.2	ASTM D445
Viscosity Index	136	ASTM D2270
Pour Point (°C)	-40	ASTM D97
Flash Point (°C)	218	ASTM D92
Noack Volatility at 250°C for 1 hour (wt %)	17.3	CEC L40-A-93
Water (ppm)	12	ASTM D3401
Bromine Number (g Br <sub>2</sub> /100 g)	0.08	IP-129
Total Acid Number (mg KOH/g)	<0.01	ASTM D974
Specific Gravity at 15.6°C	0.82	ASTM D4052
Appearance	Clear & Bright	-

EXCLUSION OF LIABILITY

Technical information contained herein is furnished without charge or obligation, and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, INEOS makes no representation about, and is not responsible or liable for the accuracy or reliability of data, nor for toxicological effects or Industrial Hygiene requirements associated with particular uses of any product described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item not supplied by INEOS. The "Properties" and "Applications" listed in this document are not specifications. They are provided as information only and in no way modify, amend, enlarge, or create any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED. The name INEOS is a trademark of INEOS Capital Limited.